



FAAST XS

Fire Alarm Aspiration Sensing Technology®

FAAST XS aspirating smoke detectors deliver highly accurate Very Early Warning Fire Detection for the smaller applications and offer extensive communication capabilities.

Features

- Provides Very Early Warning Fire Detection, as precise as 0.00029%/ft obscuration
- Three alarm levels and three sensitivity modes provide application flexibility
- User configurable 3-speed fan, allowing for maximum coverage area or minimizing on current consumption
- Ultrasonic flow sensing and chamber airflow monitoring for precise system health information
- A single device covers up to 5,000 square feet (464 sq. m)
- Dual source optical detection chamber with enhanced algorithms provide high sensitivity with greater immunity to nuisance conditions
- Patented particle separator removes large, non-fire particulate, ensuring chamber health and extending the life of the field-replaceable filter
- TCP and Serial modbus for easy integration with building management systems
- Easy configuration via USB interface, no external power needed
- Onboard Ethernet interface enables remote monitoring, configuration, web server and e-mail notifications
- Multilingual LCD user interface allows for detailed device information and interaction such as: Active faults, precise airflow monitoring, reset of airflow baseline, test/reset/isolate, and more
- Configurable air flow fault thresholds and verification period
- Convenient wiring compartment
- Status-at-a-glance provides immediate alarm, fault and airflow status



The FAAST XS aspirating smoke detector combines advanced particle separation with unique dual source optical smoke detection technology to provide highly sensitive Very Early Warning Fire Detection while providing enhanced immunity to false alarms. This technology enables FAAST XS to accurately detect incipient fire conditions as early as 60 minutes before a fire actually starts when set for Early Warning and Very Early Warning Fire Detection in applications ranging from mission critical to harsh and extreme environments.

An installed FAAST XS device can protect up to 5,000 sq. ft. (464 sq. m) in standard coverage type applications and can be monitored in several different ways, including: Serial or TCP Modbus, Ethernet over a LAN or a direct connection, or via FAAST XS's onboard USB. When connected to a LAN, FAAST XS's email server can provide email event notification to appropriate personnel. FAAST XS also communicates alarm and notifications via form C relays.

PipeIQ® is FAAST XS's intuitive design, configuration, and monitoring software. The all-in-one program can be used to create a pipe network tailored to meet site specific requirements, configure a FAAST XS device, and monitor an installed device -- including live trending and reading of historic reports.

*A complimentary download of PipeIQ is available at systemsensor.com/faast.

Agency Listings



FAAST XS Specifications

Electrical Specifications	
External Supply Voltage	18-30 VDC
Remote Reset Time	External monitor must be pulled low for a minimum of 100 ms
Power Reset	1 sec.
Operating Current	Fan High - 200mA, 4.8W; Fan Med - 151mA, 3.7W; Fan Low - 120mA, 2.1W
Alarm Current	Fan High - 230mA, 5.6W; Fan Med - 172mA, 4.2W; Fan Low - 142mA, 3.5W
Relay Contact Ratings	3.0 A @ 30 VDC, 0.5 A @ 125 VAC 5 form C, 3 AMP, programmable latching or non-latching
Operating Specifications	
Operating Temperature	32°F (0°C) to 100°F (38°C); Factory Tested to 131°F (55°C)
Sampled Air Temperature	-4°F (-20°C) to 140°F (60°C)
Humidity Range	10 to 95% (non-condensing)
Sensitivity Range	0.00029% Obs/ft to 6.25% Obs/ft (0.00095% Obs/m to 20.5% Obs/m)
IP Rating	IP30
Coverage Area	5,000 sq.ft. (464 sq.m)
Air Movement	0-4,000 ft./min. (0-1,219 m/min.)
Physical Specifications	
Height	11.0 in (279mm)
Width	9.0 in (229mm)
Depth	6.25 in (159mm)
Cable Access	3 1-inch (2.54 cm) cable entry holes on top, and back of the unit
Wire Gauge	12 AWG (2.05 mm) max. to 24 AWG (0.5 mm) min.
Maximum Single Pipe Length	180 ft. (54.9 m) <i>*all designs must be verified within PipeIQ software</i>
Total Aggregate Pipe Length	300 ft. (91.5m) <i>*all designs must be verified within PipeIQ software</i>
Outside Pipe Diameter	1.050 inches, IPS (25 mm)
Internal Pipe Diameter	0.591 to 0.827 inches (15-21 mm)
Relays	5 form C, 3 AMP, programmable latching or non-latching
Diagnostic Specifications	
Event Log	18,000 events stored
Trend Data Log	Configurable sampling period 1 minute to 1 day.
Service Log	300 custom user entries
Networking Specifications	
Communication Network	Ethernet monitoring, 6 email address alerts, TCP and Serial Modbus
Network Services	DHCP, SMTP, HTTP, MODBUS/ TCP, AutoIP, NetBIOS-NS, Serial MODBUS
Ethernet	10/100Mbps, MDI-X
Modbus	TCP or Serial RS-485
Email	6 recipients, selectable notifications
Webserver	Read Configuration, Live View, Logs
Configuration Specifications	
PipeIQ	USB or Ethernet
Modbus	Ethernet or RS-485



FAAST XS User Interface Display

The User Interface consists of 3 Alarm levels – Alert, Fire 1, and Fire 2, 10 Particulate levels, 10 Airflow indicators, 4 Fault indicators, LCD.

Ordering Information

Part No.	Description
7100X	System Sensor Conventional FAAST Fire Alarm Aspiration Sensing Technology
Accessories	
Various†	UL-Approved Pipe and Fittings

†Additional accessory information, including part numbers, can be accessed at systemsensor.com/faast



3825 Ohio Avenue • St. Charles, IL 60174
 Phone: 800-SENSOR2 • Fax: 630-377-6495
www.systemsensor.com

©2015 System Sensor.
 Product specifications subject to change without notice. Visit systemsensor.com
 for current product information, including the latest version of this data sheet.
 ASDS78701 • 9/15